

ROLL OFFS



G & H Model H06022K ROUSA
G & H Model H07522K ROUSA

designed by
G & H Manufacturing
"Buy Smart - Buy G&H"



Specifications Model	H06022K ROUSA	H07522K ROUSA
Box Length	22 foot	22 foot
Capacity	60,000 lbs	75,000 lbs
Lift & Reeving Cylinders (Interchangeable)	6" Bore x 79" Stroke x 4" Rod	7" Bore x 79" Stroke x 4" Rod
Frame Material	10" x 4" x 1/2" Rectangular Tubing ASTM A-500 Grade-C w/1/2" x 3" Bar Wear Strips	10" x 4" x 1/2" Rectangular Tubing ASTM A-500 Grade-C w/1/2" x 3" Bar Wear Strips
Cable Sheaves (all 5 interchangeable)	10" x 2.25" CRS Diameter w/Aluminum Bronze Bushings	10" x 2.25" CRS Diameter w/Aluminum Bronze Bushings
Cable	7/8" EXWRC	7/8" EXWRC
Rollers (outside)	4" diameter x 3.75" long CR Steel w/Aluminum Bronze Bushings	4" diameter x 3.75" long CR Steel w/Aluminum Bronze Bushings
Grease Fittings	At All Wear Points	At All Wear Points
Dump Angle	Approximately 50°	Approximately 50°
Front Stops	7/8" Steel Plate	7/8" Steel Plate
Rear Hinge	2.5" CR Diameter Axel	2.5" CR Diameter Axel
Front Container Lock	Automatic, 2" Diameter Pin Stress Proof CFA 311	Automatic, 2" Diameter Pin Stress Proof CFA 311
Rear Hold Down	Strap and Ratchet 7/8" Steel Hook	Strap and Ratchet 7/8" Steel Hook
Rear Ground Roller (Quick Change)	8.5" OD x 3/4" Wall x 27" Long Axel	8.5" OD x 3/4" Wall x 27" Long Axel
Bumper	Automatic Fold Up As Hoist Raises	Automatic Fold Up As Hoist Raises
Hoist Up Alarm	In Cab Buzzer	In Cab Buzzer
Back up Alarm	97 Dec	97 Dec



Mailing Address:

P.O. Box 569040
 Dallas, TX 75356

Ship to Address:

3611 Irving Boulevard
 Dallas, TX 75247

National: (800) 299-6225 • Local: (214) 631-4770 • Fax: (214) 630-0852

Options Chassis Speciation's RECOMMENDED GVWR

Front	18000 lbs
Rear	44000 lbs
Total GVWR.....	62,000 lbs
Frame Height	41" - 45"
After Frame	59"
Clear of Side Obstructions behind Cab	34"
Recommended Container Length	18' to 22'

APPROX. WEIGHT MOUNTED

Front	1800 lbs
Rear	6900 lbs
Total GVWR.....	8700

Tarpers:

- Pioneer, O'Brian, Roll Rite, Donavan

Fenders:

- Steel, Aluminum, or Plastic Fenders

Other Options:

- Inside Air Controls Joy stick or 2 levers
- Fire Extinguisher
- 24' Box Capacity 24' Hoist
- Stinger (Extendable Tail)
- Automatic Box Locks
- Auxiliary Hydraulic Power Hookups
- Pusher Type 3rd Axle
- Inside/Outside Rail
- Behind The Cab Oil Tank
- Tool Boxes: **24", 36", 48"**
- Container Stops: Fold Up/Drop In
- Rear Window Screen — Cab Guard
- Pintle Hook (**Hoist is standard with Pintle Hook Plate Drilled for Pintle Hook**)

Performance

Model 60000

- Hydraulic System 50 Gal. Side Mounted Tank
- Filtration 100 Mesh Suction S trainer/10 Micron Return Filter
- Pressure 1900 PSI
- Flow 36 GPM @ 1500 RPM
- Hoist Up: 24 Sec
- Hoist down: 14 Sec
- Cable In: 22 Sec.
- Cable Out: 12 Sec.

Model 75000

- Hydraulic System 50 Gal. Side Mounted Tank
- Filtration 100 Mesh Suction S trainer/10 Micron Return Filter
- Pressure 1900 PSI
- Flow 36 GPM @ 1500 RPM
- Hoist Up: 32 Sec.
- Hoist down: 23 Sec.
- Cable In: 25 Sec.
- Cable Out: 14 Sec.